Wax Injector

Marketed by:

>o if



CODE **MV Los Wax Injector Power Supply** AC 100 - 240 V 50 / 60 Hz **Power Consumption** 500W **Air Supply** 0.3-0.7 Mpa **Temperature Display Range** 40 - 0.95° C **Vacuum Timer** 0-20 Seconds Injection 10-250 Kpa 0.20 Seconds **Injection Timer Hold Time** 0.30 Seconds **Capacity of Wax Pot** 2.5 kg. **Dimensions (mm)** 15.5 W x 15 H x 11 L Weight 39 Kg. 120 W Heater **Temperature Controller** Included **Auto Clamping system** Included Included **Vacuum Pump**

Wax injector equipped with piston technology & as well as with the latest Micro Processor Controller. It offers a Uniqueness in the wax injection system, which is precision engineers for delivering superior accuracy based operations in a provided environment & it can be used for various types of wax injecting & deliver optimized performance.

Features:

- Digitally adjust performance from 0 to 9.5 as required.
- 2.5 kg. Wax capacity.
- User friendly interface.
- Digital display system.
- Auto clamp facility available
- ► Big auto clamp (optional)

DOIT INDUSTRIES INDIA PVT. LTD.

Certified ISO 9001:2015

Corporate Office:







